

pluie Diaper Changing Table Specifications*



	Pluie UV	Pluie Non-UV
Width (including handles)	38" (968 mm)	38" (968 mm)
Height	24" (604 mm)	24" (604 mm)
Depth	Closed: 4" (102 mm) Open (projection from wall): 24" (604 mm)	Closed: 4" (102 mm) Open (projection from wall): 24"(604 mm)
Weight	Assembled: 50 lbs (23 kg) Shipped: 64 lbs (29 kg)	Assembled: 45 lbs (20 kg) Shipped: 55 lbs (20 kg)
Style	Horizontal	Horizontal
Installation Type	Wall Mount	Wall Mount
UV-C Light System	2 UV-C light bulbs, 254 nm placed behind a protection panel	N/A
Auto Shut-Off	Yes	N/A
Sanitation Cycle Indicator Light	Yes	N/A
Changing Surface	455 sq in (2935 sq cm)	455 sq in (2935 sq cm)
Weight Capacity	Children weighing 50 lbs (23 kg) or less may be changed on Pluie. No child weighing more than 50 lbs (23 kg) should be placed or changed on Pluie. Pluie can also hold a bag weighing 25 lbs (11 kg), for a total weight capacity of 75 lbs (34 kg).	Children weighing 50 lbs (23 kg) or less may be changed on Pluie. No child weighing more than 50 lbs (23 kg) should be placed or changed on Pluie. Pluie can also hold a bag weighing 25 lbs (11 kg), for a total weight capacity of 75 lbs (34 kg).
Color	Exterior (White) Cushion (Navy)	Exterior (White) Cushion (Navy)
Multipurpose Handles for hanging diaper bag, purse	2 stainless steel handles on both sides of the table	2 stainless steel handles on both sides of the table
Security Strap	Retractable	Retractable
Table Materials	Front and Back Panels: Thermoformed and injection molded PC/ABS. Cushion: Polyurethane, water resistant and leak proof. Table Frame: Stainless Steel. Handles: Stainless Steel. Hinges: Stainless Steel. Wall Bracket: Steel. UV Light Protective Panel: Fused Silica.	Front and Back Panels: Thermoformed and injection molded PC/ABS. Cushion: Polyurethane, water resistant and leak proof. Table Frame: Stainless Steel. Handles: Stainless Steel. Hinges: Stainless Steel. Wall Bracket: Steel. UV Light Protective Panel: N/A.
Steel Table Frame	Can support up to 150 lbs (68 kg) with minimal deflection	Can support up to 150 lbs (68 kg) with minimal deflection
Open/Close Mechanism	Gas Spring	Gas Spring
ASTM, CPSIA, FCC & UL 1431 Compliant	Yes	Yes
ADA Compliant	Yes, meets ADA requirements when mounted properly	Yes, meets ADA requirements when mounted properly
Safety Messages	English (Optional Braille)	English (Optional Braille)
Liner Dispenser	N/A	N/A
Made in America	Yes	Yes
Included with Table	Mounting hardware, wall mounting template, installation instructions, window & door decals	Mounting hardware, wall mounting template, installation instructions, window & door decals
Assembly Required	Table ships fully assembled; Professional installer will need to mount on wall	Table ships fully assembled; Professional installer will need to mount on wall
Warranty	Limited five year warranty and vandalism protection policy	Limited five year warranty and vandalism protection policy
Electrical Requirements		
Supply Voltage (VAC)	120 Volt; hard-wired to electrical (power, ground, common) coming from within the wall	N/A
Frequency (Hz)	60	N/A
Maximum Current (Amps)	1	N/A

*Specifications subject to change without notice